

# TRADESMEN TAP RESEATER

## EASY INSTALLATION

1. Turn off water at mains.
2. Remove tap assembly from body of tap & remove tap valve.
3. Insert tap reseater into tap body & secure by screwing into tap thread.
4. Ensure correct depth by unscrewing centre threaded spindle so as cutting blade meets seat but is still able to move freely.
5. Carefully reseal by turning T-bar in clockwise motion with slight hand pressure.
6. To increase the depth of the cut, turn centre threaded spindle 1/8 of a turn clockwise.
7. Remove tap reseater & inspect tap seat.
8. Repeat steps 5 & 6 as necessary.
9. Replace tap assembly, turn on water & check for leaks.

## HANDY HINT

If seat is damaged beyond repair, fit new  
FIX-A-TAP® Stainless Steel Seat (Product #229007 or #222329).



A family  
owned  
Australian  
business


**Quality Assured Products**  
FIX-A-TAP® has been providing  
Australians with quality  
plumbing products since 1972.



ari.org.au

**FIX-A-TAP®**  
AUSTRALIA PTY LTD  
*The Ultimate Plumbing Solution.*  
PO Box 200 Wahroonga  
NSW 2076 Australia  
Made in China ©2025

[www.fixatap.com.au](http://www.fixatap.com.au)  
Visit our website for socials,  
plumbers, product info & more



9 312232 2094 12 >