



MODEL NO.: 982025



- ✓ **EASILY REPLACE YOUR SHOWER - NO TOOLS REQUIRED**
- ✓ **SIMPLY SCREW ON EXISTING PIPE THREADS**
- ✓ **FIVE FUNCTIONS: JET, SPRAY, ECO, BUBBLES & PAUSE**



### INSTALLATION INSTRUCTIONS

1. Ensure shower taps are turned off.
2. Remove old hose & hand piece holder.
3. Clean all connecting threads & screw holder to the wall outlet.
4. Hand tighten shower hose to shower hand piece ensuring the washer is inside the shower hose nut. Attach hose to the holder.
5. Insert hand piece into the holder & ensure correct positioning.
6. Turn on shower & inspect for leaks.

Avoid stretching or excessive kinking of the hose. If leakage occurs from the fitting, uninstall, apply threadseal tape (not included) to the exposed threads, then reinstall.

### PRODUCT SPECIFICATIONS

- Operating Temperature: Up to 80°C
- Working pressure: 150-350 kPa (21.8-50.8 psi)

### PRODUCT REQUIREMENTS

Do not overtighten nuts as damage may occur. Shower head must be installed with a maximum flow rate of 9LPM so that the product complies with requirements under AS/NZS 3500.1, clause 3.2.1.

Some showers may not be suitable when used with gravity fed heated water systems or where pressures are less than 150kPa at the outlet.

Showers with flow rates of less than 9LPM may not allow the following to function correctly:

- Low & unequal pressure supplies.
- Gravity-fed water heaters.
- Some tempering valves.
- Some instantaneous water heaters.
- Some thermostatic mixing valves.

This unit is supplied with flow restricting devices that must be maintained to ensure the 4 Star water efficiency rating achieved when tested to AS/NZS 6400 is maintained.

When water pressure is in excess of 350kPa, a pressure limiting device is required in accordance with AS/NZS 3500 recommendations, otherwise the hose warranty may be void.

This product has been granted WaterMark Certification in accordance with AS/NZS 3662. Please ensure the product is installed in compliance with Section 4 of AS/NZS 3500.1 if a dual check valve is required to prevent backflow.

**NOT TO BE USED AS A WATER LINE UNDER CONSTANT PRESSURE.**

**THREE YEAR WARRANTY** This warranty runs for three (3) years from the date of purchase.

Our products come with warranties that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure & for compensation for any other loss or damage. You are also entitled to have the goods repaired if the goods fail to be of an acceptable quality & the failure does not amount to a major failure.

**What is covered:** This warranty covers any defects in materials or workmanship with the exception of the reasons stated below. The warranty covers the product used in normal domestic use.

**What is not covered:** This warranty does not cover wear & tear to working parts, misuse or abuse. It does not cover discolourations due to exposure to sunlight or cleaning chemicals.

**Claim Procedure:** If you believe you have a legitimate claim, please contact FIX-A-TAP® Australia via our website at [www.fixatap.com.au](http://www.fixatap.com.au) to complete the warranty claim form. Alternately you can contact our office on (02) 9476 7400. Any written correspondence should be sent to: FIX-A-TAP® Australia, PO Box 200, Wahroonga, NSW 2076, Australia. Please keep your receipt for proof of purchase.

#### PlumbConnect® Plumbers Registry

To find a plumber in your area, consult our Plumbers Registry with this QR code.



For more information on recycling visit [arl.org.au](http://arl.org.au)

**FIX-A-TAP®**  
AUSTRALIA PTY LTD  
*The Ultimate Plumbing Solution*

PO Box 200 Wahroonga  
NSW 2076 Australia  
Made in China ©2025  
[www.fixatap.com.au](http://www.fixatap.com.au)

Visit our website for socials, plumbers, product info & more



A family owned Australian business

**Quality Assured Products**  
FIX-A-TAP® has been providing Australians with quality plumbing products since 1972.

