



MODEL NO.: 280336



- ✓ **EASILY REPLACE YOUR SHOWER HOSE**
- ✓ **LONG LASTING, DOUBLE LOCK STAINLESS STEEL**
- ✓ **CONNECTION SUITS ALL HAND SHOWERS**

INSTALLATION INSTRUCTIONS

1. Ensure shower taps are turned off.
2. Unscrew & discard old shower hose.
3. Hand tighten new shower hose to the shower hand piece, ensuring that the washer remains inside the shower hose nut & the male connecting threads do not damage the flow controller.
4. Screw the shower hose onto the shower holder hose connection.
5. Insert hand piece into the holder to check positioning.
6. Turn on shower & inspect for leaks.

HANDY HINT: If there is a leak at the wall outlet or the shower holder hose connection, turn off taps & remove the shower hose. Apply thread seal tape (not included) to the wall outlet thread & the shower hose connection thread. Wrap in a clockwise direction, overlap multiple turns, pulling the tape into the thread, then break tape to seal. Reconnect the hose to the wall & the shower piece.

PRODUCT SPECIFICATIONS

- Operating temperature: 10-50°C
- Working pressure: 100-500kPa (14.5-72.5psi)
- G1/2" connections to suit all hand showers
- 1.5 metre length

PRODUCT REQUIREMENTS

Do not overtighten nuts as damage may occur. Shower head must be installed with a maximum flow rate of 9LPM so that the product complies with requirements under AS/NZS 3500.1, clause 3.2.1.

Some showers may not be suitable when used with gravity fed heated water systems or where pressures are less than 150kPa at the outlet.

Showers with flow rates of less than 9LPM may not allow the following to function correctly:

- Low & unequal pressure supplies.
- Gravity-fed water heaters.
- Some tempering valves.
- Some instantaneous water heaters.
- Some thermostatic mixing valves.

This product has been granted WaterMark Certification in accordance with AS/NZS 3662. Please ensure the product is installed in compliance with Section 4 of AS/NZS 3500.1 if a dual check valve is required to prevent backflow.

NOT TO BE USED AS A WATER LINE UNDER CONSTANT PRESSURE.

FIX-A-TAP®
AUSTRALIA PTY LTD
The Ultimate Plumbing Solution

PO Box 200 Wahroonga
NSW 2076 Australia
Made in China ©2025
www.fixatap.com.au

Visit our website for socials,
plumbers, product info & more

PlumbConnect® Plumbers Registry

To find a plumber in your area, consult our Plumbers Registry with this QR code.



A family
owned
Australian
business

Quality Assured Products
FIX-A-TAP® has been providing
Australians with quality
plumbing products since 1972.

