

REPAIR



BOSTON®

GREAT VALUE SOLUTIONS



WASHING MACHINE DRAIN HOSE

2 METRES

INSTALLATION INSTRUCTIONS

- ✓ Remove old drain hose.
- ✓ Fasten BOSTON® drain hose to the washing machine. Secure with a hose clamp. Do not overtighten hose clamp.
- ✓ The opposite end of the drain hose should drain excess grey water into the laundry tub bypass.
- ✓ Check for leaks during the first test cycle of the appliance.

TECHNICAL SPECIFICATIONS

- ✓ Operating temperature up to 90°C.
- ✓ Flow rate of up to 22 litres/min.
- ✓ One end 26mm I.D. elbow to avoid hose kinking, one end 21mm I.D. end.

HANDY HINTS

- ✓ To protect your hose, avoid pulling over rough surfaces during installation.
- ✓ Do not stretch, twist or kink the hose.
- ✓ To ensure a waterproof seal, fasten hose with size 0 (#209535) hose clamps for 21mm, size OX (#209597) hose clamps for 26mm.
- ✓ It is recommended that all appliance hoses be replaced every five years.
- ✓ It is recommended that this product be installed by a licensed plumber.
- ✓ This BOSTON® drain hose features a five (5) year warranty from the date of purchase, providing the hose has been correctly installed.

The BOSTON® product warranty covers defective materials & faulty workmanship. Incorrect installation may void the product warranty.

FIX-A-TAP®
AUSTRALIA PTY LTD
The Ultimate Plumbing Solution
PO Box 200 Wahroonga
NSW Australia 2076
Made in Italy ©2025
www.fixatap.com.au

Visit our website for
socials, plumbers,
product info & more



PlumbConnect®
Plumbers Register
Find a plumber on our plumbers
registry via the QR Code

