


MIXER TAP REPAIR KIT CONTENTS

1 x 40mm Flat Mixer Cartridge, 3 x Hex Keys, 5 types of Grub Screws, 2 x Mixer Lip Seals, 2 x Friction Washers, 1 x Hot/Cold Indicator

EASY INSTALLATION

1. Turn off water at mains.
- 2.* Remove hot/cold indicator from handle.
- 3.* Use a hex key to loosen the grub screw & remove the handle.
4. Unscrew dome cover & locking nut.
5. Replace cartridge, friction washers & lip seals (make sure the cup is upwards on the top seal & downwards on the bottom seal).
6. Reassemble tap.
7. Turn on water supply & inspect for leaks.

** Instructions may vary depending on model of tap.*



SUITS MOST 40MM STANDARD MIXER TAP BRANDS

Brands include the following
(and many more):

- Hansa
- Linkware
- Novelli
- Raymor
- Brewers
- Basix
- Misty
- RAM
- Greens
- Gallery
- Some Dorf
(Serene/Belmore)

FIX-A-TAP®

AUSTRALIA PTY LTD

The Ultimate Plumbing Solution

PO Box 200 Wahroonga

NSW 2076 Australia

Made in Taiwan ©2025

www.fixatap.com.au

*Visit our website for
socials, plumbers,
product info & more*

#219954