


## MIXER TAP REPAIR KIT CONTENTS

1 x 35mm Flat Mixer Cartridge, 3 x Hex Keys,  
5 types of Grub Screws, 2 x Mixer Lip Seals,  
2 x Friction Washers, 1 x Hot/Cold Indicator

## EASY INSTALLATION

1. Turn off water at mains.
- 2.\* Remove hot/cold indicator from handle.
- 3.\* Use a hex key to loosen the grub screw & remove the handle.
4. Unscrew dome cover & locking nut.
5. Replace cartridge, friction washers & lip seals (make sure the cup is upwards on the top seal & downwards on the bottom seal).
6. Reassemble tap.
7. Turn on water supply & inspect for leaks.

*\*Instructions may vary depending on model of tap.*



# **SUITS MOST 35MM STANDARD MIXER TAP BRANDS**

Brands include the following  
(and many more):

- Hansa
- Linkware
- Novelli
- Raymor
- Brewers
- Basix
- Misty
- RAM
- Greens
- Gallery
- Stylus Venecia

**FIX-A-TAP®**

**AUSTRALIA PTY LTD**

*The Ultimate Plumbing Solution*

PO Box 200 Wahroonga

NSW 2076 Australia

Made in Taiwan ©2025

**[www.fixatap.com.au](http://www.fixatap.com.au)**

*Visit our website for  
socials, plumbers,  
product info & more*

#219947