

14-10 HEX HEAD TYPE 17



**REVOLUTIONARY
PROTECTION &
PERFORMANCE**
for corrosive environments


APPLICATION

Bremick® 14-10 Hex Head Type 17 fully threaded are designed for valley fixing cladding to timber and thin metal top hat battens.

PRODUCT ATTRIBUTES



B8 Hex Drive provides traceability and offers greater engagement and hex socket stability.



BRA® Washer designed by Bremick® and certified for cyclonic applications.

Finish high corrosion with the B8® Coating. Suitable for Category 5 corrosive environments in accordance with ISO 9223-2012 and AS4312-2008.

Type 17 Point for For drilling into timber while ensuring maximum pullout strength and a high strip torque.

DRILLING & INSTALLATION CAPACITY

Base Materials:

- Timber (JD3 min).
- Metal Battens 0.75mm BMT G550 min.

When fastening to timber, ensure a minimum thread embedment of 25mm.

When fastening metal, ensure 3 threads minimum embedment, protrude below battens / purlins.

In cyclonic regions, consult design professionals for fastener spacing.

INSTALLATION INSTRUCTIONS

1. Use a 3/8" Bremick® Hex Socket.
2. Insert the socket into a Power tool and select a drive speed of 3,000 RPM maximum.
3. Fit the screw into the socket and place the tip of the screw at the fastening position.
4. Apply firm pressure, drive until the screw has fastened. Do NOT overdrive.

14-10 HEX HEAD TYPE 17

MECHANICAL PROPERTIES

SIZE	Single Shear (kN)	Axial Tensile (kN)	Torsional (Nm)
14-10	11.6	20.3	20.8

PULL OUT VALUES


Mean Ultimate Pull Out in F5/JD4 Timber (Radiata Pine)

SIZE	20mm Embedment	25mm Embedment	30mm Embedment	35mm Embedment	40mm Embedment
14-10	4.5	6.0	6.5	6.9	7.6

Mean Ultimate Pull Out in F17/J3 Timber (Hardwood)

SIZE	20mm Embedment	25mm Embedment	30mm Embedment	35mm Embedment	40mm Embedment
14-10	5.1	7.5	9.1	9.6	11.0

Note: The above data represents characteristic capabilities obtained under laboratory conditions and are only applicable to Bremick products. The design professional must apply appropriate safety factors.



RANGE

Product Code	Description	Head Driver	Pack Qty (EA)	Finish	Length L (mm)	Thread Length TL (mm)
STHC8140256	T17 14-10x25 HEX	3/8" Hex	100	B8® COATING	25	25
STHC8140257	T17 14-10x25 HEX +SL	3/8" Hex	500	B8® COATING	25	25
STHC8140255	T17 14-10x25 HEX +SL	3/8" Hex	1,000	B8® COATING	40	40
STHC8140402	T17 14-10x40 HEX	3/8" Hex	100	B8® COATING	40	40
STHC8140408	T17 14-10x40 HEX	3/8" Hex	100	B8® COATING	75	67

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.

The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

BREMICK®

Bremick Pty Ltd

Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170

www.bremick.com.au